



Electric Automation
Automation specialists

Reference: C512-24
Code: 1SAR700100R0005

C512-24 Temperature monitoring relay
Temperature range -50...+500°C

Buy it at Electric Automation Network



Temperature monitoring relay C512-24, width 45mm, digital adjustable, 2 thresholds, exceeding/parces below, window monitoring, measuring range -50...+500°C, A1-A2=24V AC / DC, 1 c/o, 1 c/o, 1n/o

Ordering

EAN:	4013614338045
Minimum Order Quantity:	1 piece
Customs Tariff Number:	90321081

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	112 mm
Package Level 1 Height:	105 mm
Package Level 1 Length:	53 mm
Package Level 1 Gross Weight:	0.317 kg

Dimensions

Product Net Width:	45 mm
Product Net Depth:	92 mm
Product Net Height:	105.9 mm

Product Net Weight:	0.292 kg
---------------------	----------

Technical

Function:	Over- and undertemperature monitoring 1 sensor circuit Latching function
Measuring Range:	-50 ... +500 °C
Rated Control Supply Voltage (U _s):	24 V AC/DC
Output:	2 c/o (SPDT) + 1 n/o contacts
Terminal Type:	Screw Terminals
Standards:	IEC/EN 60947-5-1

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Certificates and Declarations (Document Number)

cUL Certificate:	cUL508_E140448
Declaration of Conformity - CE:	1SAD938501-0119
RoHS Information:	1SAA981005-4401
UL Certificate:	UL508_E140448

Classifications

Object Classification Code:	B
ETIM 4:	EC001446 - Temperature monitoring relay
ETIM 5:	EC001446 - Temperature monitoring relay
UNSPSC:	39121500
eClass:	7.0 27371810