



Electric Automation
Automation specialists

Reference: AF38Z-30-00-20

Code: 1SBL296001R2000

AF38Z-30-00-20 12-20VDC Contactor

Buy it at Electric Automation Network



AF38Z contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF..Z contactors include an electronic coil interface accepting a wide control voltage U_c min. ... U_c max. Only four coils cover control voltages between 24...250 V 50/60 Hz or 12...250 V DC. AF..Z contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF..Z contactors allow direct control by PLC-output ≥ 24 V DC 500 mA and obtain a reduced holding coil consumption. AF..Z contactors withstand short voltage dips and voltage sags (SEMI F47-0706 compliance) between 24...250 V 50/60 Hz AF..Z contactors have built-in surge protection and do not require additional surge suppressors The AF.. series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks. (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: DC operated for AF..Z-30-...-20 contactors. Only AF..Z-30-...-20 contactors need to respect the polarity on the coil terminals (A1+ and A2-). - Accessories: a wide range of accessories is available.

Ordering

EAN:	3471523114708
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	45 mm
Product Net Depth:	86 mm
Product Net Height:	86 mm
Product Net Weight:	0.350 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	87 mm
Package Level 1 Length:	87 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.35 kg
Package Level 1 EAN:	3471523114708
Package Level 2 Units:	45 piece
Package Level 2 Width:	250 mm
Package Level 2 Length:	300 mm
Package Level 2 Height:	315 mm
Package Level 3 Units:	1080 piece

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Standards:	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14
Rated Operational Voltage:	Main Circuit 690 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $q = 40$ °C 50 A
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 50 A (690 V) 60 °C 42 A (690 V) 70 °C 37 A
Rated Operational Current AC-3 (I_e):	(220 / 230 / 240 V) 60 °C 40 A (380 / 400 V) 60 °C 38 A (415 V) 60 °C 38 A (440 V) 60 °C 38 A (500 V) 60 °C 33 A (690 V) 60 °C 24 A
Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 11 kW (380 / 400 V) 18.5 kW (415 V) 18.5 kW (440 V) 22 kW (500 V) 22 kW (690 V) 22 kW

Rated Short-time Withstand Current (I_{cw}):	<p>at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 350 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 50 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 700 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A</p>
Maximum Breaking Capacity:	<p>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 500 A</p> <p>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 200 A</p>
Maximum Electrical Switching Frequency:	<p>AC-1 600 cycles per hour</p> <p>AC-2 / AC-4 150 cycles per hour</p> <p>AC-3 1200 cycles per hour</p>
Rated Insulation Voltage (U_i):	<p>acc. to UL/CSA 600 V</p> <p>acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V</p>
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_c):	DC Operation 12 ... 20 V
Operate Time:	<p>Between Coil De-energization and NC Contact Closing 13...98 ms</p> <p>Between Coil De-energization and NO Contact Opening 11...95 ms</p> <p>Between Coil Energization and NC Contact Opening 38...90 ms</p> <p>Between Coil Energization and NO Contact Closing 40...95 ms</p>
Connecting Capacity-Main Circuit:	<p>Flexible with Insulated Ferrule 1x 1.5...10 mm²</p> <p>Flexible with Insulated Ferrule 2x 1.5...4 mm²</p> <p>Flexible with Ferrule 1/2x 1.5...10 mm²</p> <p>Rigid 1/2x 2.5...10 mm²</p>
Connecting Capacity-Control Circuit:	<p>Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²</p> <p>Flexible with Insulated Ferrule 1x 0.75...2.5 mm²</p> <p>Flexible with Insulated Ferrule 2x 0.75...1.5 mm²</p> <p>Rigid 1/2x 1...2.5 mm²</p>
Wire Stripping Length:	<p>Control Circuit 10 mm</p> <p>Main Circuit 14 mm</p>
Degree of Protection:	<p>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20</p> <p>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20</p>
Terminal Type:	Screw Terminals

Environmental

Ambient Air Temperature:	<p>Close to Contactor for Storage -60...+80 °C</p> <p>Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C</p> <p>Close to Contactor without Thermal O/L Relay -40 ... +70 °C</p>
Maximum Operating Altitude Permissible:	3000 m

Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations acc. to IEC 60068-2-6:	5...300 Hz 4 g closed position / 2 g open position
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2008 Q1

Technical UL/CSA

General Use Rating UL/CSA:	(600 V AC) 50 A
Horsepower Rating UL/CSA:	(120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (200 ... 208 V AC) Three Phase 10 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 25 Hp (550 ... 600 V AC) Three Phase 30 Hp
Tightening Torque UL/CSA:	Control Circuit 11 in·lb Main Circuit 22 in·lb

Certificates and Declarations (Document Number)

ABS Certificate:	ABS_15-GE1349500-PDA_90682247
CB Certificate:	CB_SE_70856M1
CCC Certificate:	CCC_2010010304445623
cUL Certificate:	UL_20091124-E312527-7-1
Declaration of Conformity - CE:	1SBD250165C1000
DNV Certificate:	DNV-GL_E13871
EAC Certificate:	EAC_RU C-FR ME77 B01010
GL Certificate:	DNV-GL_E13871
GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
LR Certificate:	LRS_1300087E1
RINA Certificate:	RINA_ELE084013XG
RMRS Certificate:	RMRS_1400682124
RoHS Information:	1SBD251012E1000

Classifications

ETIM 5:	EC000066 - Magnet contactor, AC-switching
UNSPSC:	39121529