



**Electric Automation**  
Automation specialists

Reference: GA75-10-00  
Code: 1SBL411025R8000

GA75-10-00 220-230V 50Hz / 230-240V  
60Hz Contactor

Buy it at [Electric Automation Network](#)



GA75 contactors are designed for DC circuit switching. Arc suppression is more difficult in DC than in AC. To choose a contactor, it is necessary to know the current and voltage to be broken as well as the L/R time constant of the power circuit to be controlled. GA75 contactors are of the block type design. - Main poles: the contactors are fitted with arc chutes with permanent magnets specially designed for DC breaking. The three contactor paths are arranged in series via two supplied and fitted insulated connections (25 mm<sup>2</sup>). The GA75 are "single-pole" devices for which the connection polarities indicated next to the connection terminals must be respected. Furthermore, they are marked 1L1 for the positive terminal and 2T1 for the negative terminal. - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available

### Ordering

EAN:	3471522099808
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

### Dimensions

Product Net Width:	70 mm
Product Net Depth:	108 mm
Product Net Height:	132 mm
Product Net Weight:	1.220 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	140 mm
Package Level 1 Length:	146 mm
Package Level 1 Height:	96 mm
Package Level 1 Gross Weight:	1.22 kg
Package Level 1 EAN:	3471522099808
Package Level 2 Units:	63 piece

## Technical

Number of Main Contacts NO:	1
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Rated Operational Voltage:	Main Circuit 600 V
Conventional Free-air Thermal Current ( $I_{th}$ ):	acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ °C}$ 125 A
Short-Circuit Protective Devices:	gG Type Fuses 160 A
Rated Short-time Withstand Current ( $I_{cw}$ ):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 650 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 135 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 370 A
Maximum Electrical Switching Frequency:	300 cycles per hour
Rated Operational Current DC-1 ( $I_e$ ):	(440 V) 55 °C 100 A
Rated Operational Current DC-3 ( $I_e$ ):	(440 V) 85 A
Rated Operational Current DC-5 ( $I_e$ ):	(220 V) 85 A (440 V) 35 A
Rated Insulation Voltage ( $U_i$ ):	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Mechanical Durability:	10 million
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55\text{ °C}$ ) °C
Rated Control Circuit Voltage ( $U_c$ ):	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V

Coil Consumption:	<p>Pull-in at Max. Rated Control Circuit Voltage 50 Hz 180 V·A  Pull-in at Max. Rated Control Circuit Voltage 60 Hz 210 V·A  Holding at Max. Rated Control Circuit Voltage 60 Hz 18 V·A  Holding at Max. Rated Control Circuit Voltage 60 Hz 5.5 W  Holding at Max. Rated Control Circuit Voltage 50 Hz 18 V·A  Holding at Max. Rated Control Circuit Voltage 50 Hz 5.5 W  Average Holding Value 50 / 60 Hz 18 V·A  Average Holding Value 50 / 60 Hz 5.5 W  Average Pull-in Value 50 Hz 190 V·A  Average Pull-in Value 60 Hz 180 V·A</p>
Operate Time:	<p>Between Coil Energization and NO Contact Closing 8 ... 27 ms  Between Coil De-energization and NO Contact Opening 4 ... 11 ms</p>
Connecting Capacity-Main Circuit:	<p>Flexible with Cable End6 ... 16 mm<sup>2</sup>  Rigid Cable6 ... 25 mm<sup>2</sup></p>
Connecting Capacity-Auxiliary Circuit:	<p>Flexible with Cable End0.75 ... 2.5 mm<sup>2</sup>  Rigid Cable1 ... 4 mm<sup>2</sup></p>
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Connecting terminals (delivered in open position) Main poles:	M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector
Terminal Type:	Screw Terminals

## Environmental

Ambient Air Temperature:	<p>Near Contactor for Operation in Free Air (0.85 ... 1.1 U<sub>c</sub>)  -40 ... +55 °C  Near Contactor for Operation in Free Air (U<sub>c</sub>) -40 ... +70 °C  Close to Contactor for Storage -60 ... +80 °C</p>
Climatic Withstand:	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible:	3000 m
RoHS Status:	No declaration needed

## Certificates and Declarations (Document Number)

CCC Certificate:	CCC_2011010304454200
CSA Certificate:	CSA_1033838_LR056745
Declaration of Conformity - CE:	1SBD250815C2000
GOST Certificate:	GOST_POCCFRME77B07175
RoHS Information:	1SBC101059D0201

## Classifications

ETIM 5:	EC002552 - Power contactor, DC switching
UNSPSC:	39121529