



Electric Automation
Automation specialists

Reference: AF75-40-00RT
Code: 1SBL417210R6900

AF75-40-00RT 48-130V 50Hz / 48-130V
60Hz / 48-130V DC Contactor

Buy it at Electric Automation Network



AF75 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The AF... contactors are fitted with an electronic coil interface which accepts a wide control voltage range, on AC 50/60 Hz or DC supplies. The same contactor can accept various supply voltages according to the different countries where the electrical equipment will be installed, or some fluctuation in the control voltage due to the local supply or network. The AF... contactors are also fully suitable for operation in AC or DC control circuit liable to voltage interruptions or voltage dip risks. Advantages: - Wide voltage range, e.g. 100 ... 250 V AC and DC - Can manage large voltage variations - Reduced power consumption - Very distinct closing and opening - Noise free - Can withstand voltage interruptions or voltage dips in the control supply (≤ 20 ms). The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.

Ordering

EAN:	3471522245595
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	92 mm
Product Net Depth:	119.5 mm
Product Net Height:	110 mm
Product Net Weight:	1.420 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	142 mm
Package Level 1 Length:	190 mm
Package Level 1 Height:	136 mm
Package Level 1 Gross Weight:	1.42 kg
Package Level 1 EAN:	3471522245595
Package Level 2 Units:	8 piece

Technical

Terminal Type:	Ring-Tongue Terminals
----------------	-----------------------

Certificates and Declarations (Document Number)

GOST Certificate:	GOST_POCCFRME77B07175
-------------------	-----------------------

Classifications

ETIM 5:	EC000066 - Magnet contactor, AC-switching
UNSPSC:	39121529