



**Electric Automation**  
Automation specialists

Reference: OT630KGCC3A  
Code: 1SCA022297R6600

OT630KGCC3A Safety switch

Buy it at [Electric Automation Network](#)



Safety switch 3-p.400V AC23A 315kW AC22A 570A Plastic enclosure IP65 Yellow-red Pistol handle

### Ordering

EAN:	6417019071992
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85371099

### Dimensions

Product Net Width:	560 mm
Product Net Height:	760 mm
Product Net Depth:	250 mm
Product Net Weight:	26 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	565 mm
Package Level 1 Height:	330 mm
Package Level 1 Length:	770 mm
Package Level 1 Gross Weight:	26.7 kg
Package Level 1 EAN:	6417019071992

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

## Additional Information

Cable Entry Position:	Bottom
Cable Outlets Per Side:	2 x II-flange
Conventional Thermal Current ( $I_{the}$ ):	Fully Enclosed 460 A
Degree of Protection:	acc. to IEC 60529 IP65
Enclosure Material:	Plastic
IIT Publishing Status:	Level 0 - Information enabled
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	2
Number of Poles:	3
Order Multiple:	1 piece
Pollution Degree:	3
Position of Line Terminals:	Bottom In - Bottom Out
Position of PE Terminals:	Bottom In - Bottom Out
Product Main Type:	OT630
Product Name:	Safety switch
Rated Operational Current AC-22A ( $I_e$ ):	(500 V) 570 A (690 V) 570 A
Rated Operational Current AC-23A ( $I_e$ ):	(380 ... 415 V) 570 A (500 V) 570 A (690 V) 570 A
Rated Operational Power AC-23A ( $P_e$ ):	(220 ... 240 V) 180 kW (400 V) 315 kW (500 V) 400 kW (690 V) 560 kW
Rated Operational Voltage:	1000 V

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC340006C0201
Declaration of Conformity - CE:	1SCC340029D0203
RoHS Information:	1SCC301149D0202

## Classifications

ETIM 5:	EC000249 - Protection switch disconnecter housing
Object Classification Code:	Q

