



Electric Automation
Automation specialists

Reference: OT400U03
Code: 1SCA022747R6490

OT400U03 Non-fusible disconnect switch

Buy it at [Electric Automation Network](#)



Handle and shaft must be ordered separately.

Ordering

EAN:	6417019242613
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	221 mm
Product Net Height:	220 mm
Product Net Depth:	85 mm
Product Net Weight:	3.06 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	240 mm
Package Level 1 Height:	120 mm
Package Level 1 Length:	290 mm
Package Level 1 Gross Weight:	3.06 kg

Package Level 1 EAN:	6417019242613
----------------------	---------------

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---------------------------------------------------------------------------------------

Technical UL/CSA

Ampere Rating UL/CSA:	400 A
Horsepower Rating UL/CSA:	(acc. to UL 240 V) 125 Hp (acc. to UL 480 V) 250 Hp (acc. to UL 600 V) 350 Hp

Additional Information

Earthing Switch Type:	No Additional Type
Handle Type:	None
IIT Publishing Status:	Level 0 - Information enabled
Includes:	None
Mounting Type:	Normal
Number of Poles:	3
Operating Mechanism:	Mechanism at the end of the switch
Operating Mode:	Front Operated
Pollution Degree:	3
Power Loss:	10 W
Product Main Type:	OT400U
Product Name:	Switch-disconnector
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-22A (I_e):	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 15 kiloampere rms
Special Functions:	No
Standards:	IEC&UL
Terminal Type:	Lug terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC301020C0201
Declaration of Conformity - CE:	1SCC301138D0202

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q