



Electric Automation
Automation specialists

Reference: OTM400E4CM230C
Code: 1SCA022847R3250

OTM400E4CM230C MOTORIZED C/O
SWITCH

Buy it at Electric Automation Network



Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

Ordering

EAN:	6417019298009
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	367 mm
Product Net Height:	185 mm
Product Net Depth:	235 mm
Product Net Weight:	12.5 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	255 mm
Package Level 1 Height:	253 mm
Package Level 1 Length:	460 mm

Package Level 1 Gross Weight:	11.44 kg
Package Level 1 EAN:	6417019298009

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 400 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 400 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	4
Operating Mechanism:	Mechanism at the end of the switch
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	10 W
Product Main Type:	OTM400_CM
Product Name:	MOTORIZED C/O SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current AC-21A (I_e):	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A (I_e):	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 132 kW (400 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Rated Operational Voltage:	1000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 15 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
Declaration of Conformity - CE:	1SCC303013D0202
RoHS Information:	1SCC303036D0202

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q