



Electric Automation
Automation specialists

Reference: OT16F4C
Code: 1SCA104831R1001

OT16F4C CHANGE-OVER SWITCH

Buy it at Electric Automation Network



Handle and shaft has to be ordered separately

Ordering

EAN:	6417019389752
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	96 mm
Product Net Height:	68 mm
Product Net Depth:	68 mm
Product Net Weight:	0.31 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	80 mm
Package Level 1 Height:	79 mm
Package Level 1 Length:	108 mm
Package Level 1 Gross Weight:	0.31 kg
Package Level 1 EAN:	6417019389752

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Technical UL/CSA

Ampere Rating UL/CSA:	16 A
Horsepower Rating UL/CSA:	(acc. to UL 200 V) 3 Hp (acc. to UL 208 V) 3 Hp (acc. to UL 240 V) 5 Hp (acc. to UL 480 V) 10 Hp (acc. to UL 600 V) 10 Hp

Additional Information

Cable Cross-Section:	0.75...10 mm ²
Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 25 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 25 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	4
Operating Mechanism:	Mechanism between the poles
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	0.3 W
Product Main Type:	OT16_C
Product Name:	CHANGE-OVER SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	750 V
Rated Operational Current AC-21A (I_e):	(500 V) 16 A (690 V) 16 A
Rated Operational Current AC-22A (I_e):	(500 V) 16 A (690 V) 16 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 10 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 3 kW (400 V) 7,15 kW (415 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW
Rated Operational Voltage:	750 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 0.5 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
------------------------------------	-----------------

Declaration of Conformity - CE:	1SCC303019D0201
RoHS Information:	1SCC301183D0201

Classifications

ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	Q