



Electric Automation
Automation specialists

Reference: OT100F3C
Code: 1SCA105008R1001

OT100F3C CHANGE-OVER SWITCH

Buy it at Electric Automation Network



Handle and shaft has to be ordered separately

Ordering

EAN:	6417019391397
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	140 mm
Product Net Height:	100 mm
Product Net Depth:	86 mm
Product Net Weight:	0.9 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	102 mm
Package Level 1 Height:	103 mm
Package Level 1 Length:	205 mm
Package Level 1 Gross Weight:	0.9 kg
Package Level 1 EAN:	6417019391397

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Cable Cross-Section:	10...70 mm ²
Conventional Free-air Thermal Current (I_{th}):	q = 40 °C 115 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 115 A
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Operating Mechanism:	Mechanism between the poles
Order Multiple:	1 piece
Pollution Degree:	3
Position of Line Terminals:	Top In - Bottom Out
Power Loss:	4 W
Product Main Type:	OT100_C
Product Name:	CHANGE-OVER SWITCH
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	750 V
Rated Operational Current AC-21A (I_e):	(500 V) 100 A (690 V) 100 A
Rated Operational Current AC-22A (I_e):	(500 V) 100 A (690 V) 100 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 80 A (500 V) 60 A (690 V) 40 A
Rated Operational Power AC-23A (P_e):	(220 ... 240 V) 22 kW (400 V) 37 kW (500 V) 37 kW (690 V) 37 kW
Rated Operational Voltage:	750 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 2.5 kiloampere rms

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SCC303003C0201
Declaration of Conformity - CE:	1SCC303021D0201
RoHS Information:	1SCC301183D0201

Classifications

E-number:	3171265
ETIM 5:	EC000216 - Switch disconnecter

Object Classification Code:

Q