




Electric Automation
Automation specialists

Reference: OT2000E04K
Code: 1SCA108362R1001

OT2000E04K switch-disconnector

Buy it at Electric Automation Network



Including a black Test-OFF-ON plastic handle and shaft as standard. The handle is padlockable in the OFF-position.

Ordering

| | |
|-------------------------|---------------|
| EAN: | 6417019416793 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85365080 |

Dimensions

| | |
|---------------------|---------|
| Product Net Width: | 599 mm |
| Product Net Height: | 376 mm |
| Product Net Depth: | 127 mm |
| Product Net Weight: | 27.8 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 580 mm |
| Package Level 1 Height: | 200 mm |
| Package Level 1 Length: | 780 mm |
| Package Level 1 Gross Weight: | 47.8 kg |
| Package Level 1 EAN: | 6417019416793 |

Environmental

| | |
|--------------|---|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4 |
|--------------|---|

Additional Information

| | |
|---|------------------------------------|
| Conventional Free-air Thermal Current (I_{th}): | q = 40 °C 2000 A |
| Earthing Switch Type: | No Additional Type |
| Handle Type: | Direct |
| IIT Publishing Status: | Level 0 - Information enabled |
| Includes: | Handle and Shaft |
| Mounting Type: | Normal |
| Number of Poles: | 4 |
| Operating Mechanism: | Mechanism at the end of the switch |
| Operating Mode: | Front Operated |
| Order Multiple: | 1 piece |
| Pollution Degree: | 3 |
| Power Loss: | 55 W |
| Product Main Type: | OT2000 |
| Product Name: | Switch-disconnector |
| Rated Impulse Withstand Voltage (U_{imp}): | 12 kV |
| Rated Insulation Voltage (U_i): | 1000 V |
| Rated Operational Current AC-21A (I_e): | (690 V) 2000 A |
| Rated Operational Current AC-22A (I_e): | (500 V) 2000 A (690 V) 2000 A |
| Rated Operational Voltage: | 1000 V |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 55 kiloampere rms |
| Special Functions: | No |
| Standards: | IEC |
| Terminal Type: | Lug terminals |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SCC301020C0201 |
| Declaration of Conformity - CE: | 1SCC301176D0201 |

Classifications

| | |
|-----------------------------|--------------------------------|
| ETIM 5: | EC000216 - Switch disconnector |
| Object Classification Code: | Q |