



Electric Automation
Automation specialists

Reference: T1N160
Code: 1SDA050931R1

T1N 160 TMD63-630 4p F FC Cu
(1 \times 70mm²)

Buy it at Electric Automation Network



C.BREAKER TMAX T1N 160 FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu 70mm² AND THERMOMAGNETIC RELEASE TMD R 63-630 A

Ordering

EAN:	8015644513436
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090
Replacement Product ID (NEW):	1SDA067422R1

Dimensions

Product Net Width:	102 mm
Product Net Height:	130 mm
Product Net Depth:	70 mm
Product Net Weight:	1.3 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	128 mm
Package Level 1 Height:	135 mm
Package Level 1 Length:	143 mm

Package Level 1 Gross Weight:	1.4 kg
Package Level 1 EAN:	8015644513436

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

Additional Information

Electrical Durability:	8000 cycle 120 cycles per hour
IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	25000 cycle 240 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 4,3 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	63 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 37,5 kA (230 V AC) 37,5 kA (380 V AC) 27 kA (400 V AC) 27 kA (415 V AC) 27 kA (440 V AC) 11 kA (500 V AC) 7,5 kA (690 V AC) 3 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 5 kA (230 V AC) 5 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 22 kA (500 V AC) 15 kA (690 V AC) 6 kA (250 V DC) 2 Poles in Series 36 kA (250 V DC) 3 Poles in Series 40 kA (500 V DC) 3 Poles in Series 36 kA
Rated Uninterrupted Current (I_u):	160 A
Release Type:	TM
Standards:	IEC 60947
Sub-type:	T1

Suitable For:	T1
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front for Copper Cables
Test Voltage at Industrial Frequency for 1 Minute:	3000 V
Test Voltage Max (U_{test}):	3000 V
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203
Data Sheet, Technical Information (Part 2):	1SDM000030R0001
Declaration of Conformity - CE:	1SDL000165R0001
GL Certificate:	1SDL000163R0058
RoHS Information:	1SDL000200R0001

Classifications

E-nummer:	3180074
Object Classification Code:	Q
UNSPSC:	39121100