



Electric Automation
Automation specialists

Reference: T2H160
Code: 1SDA051051R1

T2H 160 TMD2-20 4p F F

Buy it at Electric Automation Network



C.BREAKER TMAX T2H 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 2-20 A

Ordering

EAN:	8015644514730
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	120 mm
Product Net Height:	130 mm
Product Net Depth:	70 mm
Product Net Weight:	1.45 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	128 mm
Package Level 1 Height:	135 mm
Package Level 1 Length:	143 mm
Package Level 1 Gross Weight:	1.55 kg

Package Level 1 EAN:	8015644514730
----------------------	---------------

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

Additional Information

Electrical Durability:	8000 cycle 120 cycles per hour
IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	25000 cycle 240 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 2,5 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	2 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	800 V
Rated Operational Voltage:	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 55 kA (500 V AC) 36 kA (690 V AC) 8 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 10 kA (230 V AC) 10 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 55 kA (500 V AC) 36 kA (690 V AC) 8 kA (250 V DC) 2 Poles in Series 70 kA (250 V DC) 3 Poles in Series 85 kA (500 V DC) 3 Poles in Series 70 kA
Rated Uninterrupted Current (I_u):	160 A
Release Type:	TM
Standards:	IEC 60947
Sub-type:	T2
Suitable For:	T2

Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage at Industrial Frequency for 1 Minute:	3000 V
Test Voltage Max (U_{test}):	3000 V
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203
Data Sheet, Technical Information (Part 2):	1SDM000030R0001
Declaration of Conformity - CE:	1SDL000165R0002
GL Certificate:	1SDL000163R0059
RoHS Information:	1SDL000200R0001

Classifications

Object Classification Code:	Q
UNSPSC:	39121100