



**Electric Automation**  
Automation specialists

Reference: T4N320  
Code: 1SDA054117R1

T4N 320 PR221DS-LS/I In=320 3p F F

Buy it at Electric Automation Network



C.BREAKER TMAX T4N 320 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 320

### Ordering

EAN:	8015644552169
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

### Dimensions

Product Net Width:	105 mm
Product Net Height:	205 mm
Product Net Depth:	103.5 mm
Product Net Weight:	3.5 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Length:	285 mm
Package Level 1 Gross Weight:	3.5 kg

Package Level 1 EAN:	8015644552169
----------------------	---------------

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007-01-01
--------------	--

## Additional Information

Electrical Durability:	6000 cycle 120 cycles per hour
IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	20000 cycle 240 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 17,6 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current ( $I_n$ ):	320 A
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Rated Insulation Voltage ( $U_i$ ):	1000 V
Rated Operational Voltage:	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 20 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(220 V AC) 7 kA (230 V AC) 7 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 36 kA (250 V DC) 3 Poles in Series 25 kA (500 V DC) 3 Poles in Series 16 kA
Rated Uninterrupted Current ( $I_u$ ):	320 A
Release Type:	EL
Standards:	IEC 60947
Sub-type:	T4
Suitable For:	T4

Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage at Industrial Frequency for 1 Minute:	3500 V
Test Voltage Max ( $U_{test}$ ):	3500 V
Version:	F

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203
Declaration of Conformity - CE:	1SDL000165R0004
RoHS Information:	1SDL000200R0001

## Classifications

E-nummer:	3180305
ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q
UNSPSC:	39121100