



Electric Automation
Automation specialists

Reference: T5V400
Code: 1SDA054485R1

T5V 400 TMA 320-3200 4p F F
InN=100%In

Buy it at Electric Automation Network



C.BREAKER TMAX T5V 400 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 320 I3=1600...3200 A FULLY RATED NEUTRAL

Ordering

EAN:	8015644555825
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	186 mm
Product Net Height:	205 mm
Product Net Depth:	103.5 mm
Product Net Weight:	5.8 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Length:	285 mm
Package Level 1 Gross Weight:	5.8 kg

Package Level 1 EAN:	8015644555825
----------------------	---------------

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

Additional Information

Electrical Durability:	7000 cycle 60 cycles per hour
IIT Publishing Status:	Level 0 - Information enabled
Mechanical Durability:	20000 cycle 120 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 13,6 W
Product Main Type:	SACE Tmax T
Product Name:	Automatic Circuit Breaker
Product Type:	CB
Rated Current (I_n):	320 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Voltage:	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 200 kA (400 V AC) 200 kA (415 V AC) 200 kA (440 V AC) 180 kA (500 V AC) 150 kA (690 V AC) 80 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 5 A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 20 kA (230 V AC) 20 kA (380 V AC) 200 kA (400 V AC) 200 kA (415 V AC) 200 kA (440 V AC) 180 kA (500 V AC) 150 kA (660 V AC) 80 kA (690 V AC) 80 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 2 Poles in Series 65 kA (750 V DC) 3 Poles in Series 50 kA
Rated Uninterrupted Current (I_u):	400 A
Release Type:	TM
Standards:	IEC 60947
Sub-type:	T5

Suitable For:	T5
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210004D0203
Declaration of Conformity - CE:	1SDL000165R0005
RoHS Information:	1SDL000200R0001

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q
UNSPSC:	39121100