



Electric Automation
Automation specialists

Reference: E1N/MS800
Code: 1SDA058941R1

E1N/MS 800 3p W MP new

Buy it at Electric Automation Network



SACE EMAX MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR E1N/MS 800A
THREE-POLE NEW

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644613006 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|----------|
| Product Net Width: | 324 mm |
| Product Net Height: | 461 mm |
| Product Net Depth: | 396.5 mm |
| Product Net Weight: | 44 kg |

Container Information

| | |
|-------------------------------|---------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 515 mm |
| Package Level 1 Height: | 600 mm |
| Package Level 1 Length: | 515 mm |
| Package Level 1 Gross Weight: | 55 kg |

| | |
|----------------------|---------------|
| Package Level 1 EAN: | 8015644609139 |
|----------------------|---------------|

Additional Information

| | |
|--|---|
| Electrical Durability: | 10000 cycle 30 cycles per hour |
| Mechanical Durability: | 25000 cycle 60 cycles per hour |
| Number of Poles: | 3 |
| Power Loss: | at Rated Operating Conditions per Pole 95 W |
| Product Main Type: | SACE Emax |
| Product Name: | Automatic Circuit Breaker |
| Product Type: | SDMP |
| Rated Current (I_n): | 800 A |
| Rated Impulse Withstand Voltage (U_{imp}): | 12 kV |
| Rated Insulation Voltage (U_i): | 1000 V |
| Rated Operational Current (I_e): | 800 A |
| Rated Operational Voltage: | 690 V AC 250 V DC |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 50 kA for 3 s 36 kA |
| Rated Uninterrupted Current (I_u): | 800 A |
| Rated Voltage (U_r): | 690 V |
| Standards: | IEC 60947 |
| Sub-type: | E1 |
| Terminal Connection Type: | Withdrawable Circuit-Breakers |
| Version: | W |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SDC200006D0209 |
| Declaration of Conformity - CE: | 1SDL000165R0013 |

Classifications

| | |
|-----------------------------|---|
| ETIM 4: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| ETIM 5: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| Object Classification Code: | Q |
| UNSPSC: | 39120000 |