



Electric Automation
Automation specialists

Reference: X1N1250
Code: 1SDA062527R1

X1N 1250 PR332/P LI In=1250A 4p W MP

Buy it at Electric Automation Network



MOVING PART FOR CIRCUIT-BREAKER EMAX X1N 1250 FOUR-POLE WITH SOLID-STATE RELEASE IN AC PR332/P-LI R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

| | |
|-------------------------|---------------|
| EAN: | 8015644650735 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362090 |

Dimensions

| | |
|---------------------|--------|
| Product Net Width: | 354 mm |
| Product Net Height: | 343 mm |
| Product Net Depth: | 254 mm |
| Product Net Weight: | 18 kg |

Container Information

| | |
|-------------------------|---------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 385 mm |
| Package Level 1 Height: | 350 mm |
| Package Level 1 Length: | 400 mm |

| | |
|-------------------------------|---------------|
| Package Level 1 Gross Weight: | 19.5 kg |
| Package Level 1 EAN: | 8015644609139 |

Environmental

| | |
|--------------|---|
| RoHS Status: | Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2 |
|--------------|---|

Additional Information

| | |
|--|--|
| Number of Poles: | 4 |
| Power Loss: | at Rated Operating Conditions per Pole 253 W |
| Product Main Type: | SACE Emax |
| Product Name: | Automatic Circuit Breaker |
| Product Type: | CBMP |
| Rated Current (I_n): | 1250 A |
| Rated Operational Voltage: | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (220 V AC) 50 kA (230 V AC) 50 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 42 kA (660 V AC) 42 kA (690 V AC) 42 kA |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 42 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (220 V AC) 65 kA (230 V AC) 65 kA (380 V AC) 65 kA (400 V AC) 65 kA (415 V AC) 65 kA (440 V AC) 65 kA (500 V AC) 50 kA (525 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA |
| Rated Uninterrupted Current (I_u): | 1250 A |
| Rated Voltage (U_r): | 690 V |
| Release Type: | EL |
| Standards: | IEC 60947 |
| Sub-type: | X1 |
| Terminal Connection Type: | Withdrawable Circuit-Breakers |
| Version: | W |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 1SDC200009D0203 |
|------------------------------------|-----------------|

| | |
|---------------------------------|-----------------|
| Declaration of Conformity - CE: | 1SDL000165R0018 |
| RoHS Information: | 1SDL000203R0001 |

Classifications

| | |
|-----------------------------|---|
| ETIM 4: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| ETIM 5: | EC000228 - Power circuit-breaker for trafo/generator/ installation prot. |
| Object Classification Code: | Q |
| UNSPSC: | 39120000 |