



**Electric Automation**  
Automation specialists

Reference: X1L1250  
Code: 1SDA062554R1

X1L 1250 PR332/P LI In=1250A 3p W MP

Buy it at Electric Automation Network



MOVING PART FOR CIRCUIT-BREAKER EMAX X1L 1250 THREE-POLE WITH SOLID-STATE RELEASE IN AC PR332/P-LI R 1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

### Ordering

EAN:	8015644651008
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

### Dimensions

Product Net Width:	284 mm
Product Net Height:	343 mm
Product Net Depth:	254 mm
Product Net Weight:	14 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	335 mm
Package Level 1 Height:	350 mm
Package Level 1 Length:	380 mm

Package Level 1 Gross Weight:	15.5 kg
Package Level 1 EAN:	8015644609139

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2
--------------	---

## Additional Information

Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 354 W
Product Main Type:	SACE Emax
Product Name:	Automatic Circuit Breaker
Product Type:	CBMP
Rated Current ( $I_n$ ):	1250 A
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (660 V AC) 45 kA (690 V AC) 45 kA
Rated Short-time Withstand Current ( $I_{cw}$ ):	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 130 kA (500 V AC) 100 kA (525 V AC) 100 kA (660 V AC) 60 kA (690 V AC) 60 kA
Rated Uninterrupted Current ( $I_u$ ):	1250 A
Rated Voltage ( $U_r$ ):	690 V
Release Type:	EL
Standards:	IEC 60947
Sub-type:	X1
Terminal Connection Type:	Withdrawable Circuit-Breakers
Version:	W

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC200009D0203
------------------------------------	-----------------

Declaration of Conformity - CE:	1SDL000165R0018
RoHS Information:	1SDL000203R0001

## Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q
UNSPSC:	39120000