Reference: E4.2V/MS2000
Code: 1SDA073455R1

E4.2V/MS 2000 4p F HR

Buy it at Electric Automation Network

C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E4.2V/MS 2000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL

Ordering

EAN:	8015644773052
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	510 mm
Product Net Height:	371 mm
Product Net Depth:	270 mm
Product Net Weight:	81 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	683 mm
Package Level 1 Height:	618 mm
Package Level 1 Length:	420 mm
Package Level 1 Gross Weight:	77 kg

Package Level 1 EAN:	8015644609139

Additional Information

Current Type:	AC
Electrical Durability:	Ue =< 440 V 10000 cycle Ue = 500 ... 690 V 10000 cycle 20 cycles per hour
Mechanical Durability:	20000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	100 %
Number of Poles:	4
Product Main Type:	SACE Emax 2
Product Name:	Switch-disconnector
Product Type:	SD
Rated Current (I_n):	2000 A
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	AC 1000 V
Rated Operational Voltage:	690 V AC
Rated Short-time Withstand Current (I_{cw}):	for 1 s 100 kA for 3 s 75 kA
Rated Uninterrupted Current (I_u):	2000 A
Rated Voltage (U_r):	690 V
Standards:	IEC 60947
Sub-type:	E4.2
Terminal Connection Type:	Rear flat Horizontal
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC200023D0204
Declaration of Conformity - CE:	1SDL000165R0021

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q