Reference: E6.2H/MS4000
Code: 1SDA073463R1

E6.2H/MS 4000 4p F HR

Buy it at Electric Automation Network

C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E6.2H/MS 4000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL

Ordering

EAN:	8015644773137
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	888 mm
Product Net Height:	371 mm
Product Net Depth:	270 mm
Product Net Weight:	112 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	1058 mm
Package Level 1 Height:	625 mm
Package Level 1 Length:	420 mm
Package Level 1 Gross Weight:	134 kg
Package Level 1 EAN:	8015644609139

Additional Information

Current Type:	AC
Electrical Durability:	Ue =< 440 V 4000 cycle Ue = 500 ... 690 V 4000 cycle 10 cycles per hour
Mechanical Durability:	12000 cycle 60 cycles per hour
Neutral Pole Current ([%Iu]):	50 %
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 309 W
Product Main Type:	SACE Emax 2
Product Name:	Switch-disconnector
Product Type:	SD
Rated Current (I_n):	4000 A
Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	AC 1000 V
Rated Operational Voltage:	690 V AC
Rated Short-time Withstand Current (I_{cw}):	for 1 s 100 kA for 3 s 100 kA
Rated Uninterrupted Current (I_u):	4000 A
Rated Voltage (U_r):	690 V
Standards:	IEC 60947
Sub-type:	E6.2
Terminal Connection Type:	Rear flat Horizontal
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC200023D0204
Declaration of Conformity - CE:	1SDL000165R0022

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/ installation prot.
Object Classification Code:	Q