



Electric Automation
Automation specialists

Reference: XLP1-6M10
Code: 1SEP101891R0004

250 A incl. 6xM10x20 bolts

Buy it at Electric Automation Network



XLP1-6M10 250 A incl. 6xM10x20 bolts

Ordering

EAN:	7025840020325
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363000

Dimensions

Product Net Width:	0.185 m
Product Net Height:	0.27 m
Product Net Depth:	0.116 m
Product Net Weight:	1.8 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.185 m
Package Level 1 Height:	0.27 m
Package Level 1 Length:	0.116 m
Package Level 1 Gross Weight:	1.8 kg

Package Level 2 EAN:	7025840020325
----------------------	---------------

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

Additional Information

Degree of Protection:	acc. to IEC 60529 Front IP30
Frequency (f):	50/60 Hz
Fuse Protected Short-Circuit Making:	50 kA
Fuse Protected Short-Circuit Withstand:	50 kA
Fuse Size:	1
Fuse System:	DIN
Fuse Type:	NH
Handle Type:	detach
Number of Poles:	3
Product Main Type:	EasyLine
Product Name:	Fuse Switch Disconnecter
Rated Current (I_n):	Main Circuit 250 A
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Rated Operational Current AC-22B (I_e):	(500 V) 160 A
Rated Operational Current AC-23B (I_e):	(500 V) 250 A

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SEC312011B0202
------------------------------------	-----------------

Classifications

ETIM 4:	EC001040 - Fuse switch disconnecter
ETIM 5:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q