



**Electric Automation**  
Automation specialists

Reference: XLP1  
Code: 1SEP101912R0004

250 A incl. A40/120 adapter incl. 3xM10 bolts, cable above

[Buy it at Electric Automation Network](#)



XLP1-A40/120-3M10

### Ordering

EAN:	7025840016496
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363000

### Dimensions

Product Net Width:	0.185 m
Product Net Height:	0.27 m
Product Net Depth:	0.196 m
Product Net Weight:	2.75 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.185 m
Package Level 1 Height:	0.27 m
Package Level 1 Length:	0.196 m
Package Level 1 Gross Weight:	2.75 kg

Package Level 2 EAN:	7025840016496
----------------------	---------------

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

## Additional Information

Degree of Protection:	acc. to IEC 60529 Front IP30
Frequency ( $f$ ):	50/60 Hz
Fuse Protected Short-Circuit Making:	50 kiloampere rms
Fuse Protected Short-Circuit Withstand:	50 kiloampere rms
Fuse Size:	1
Fuse System:	DIN
Fuse Type:	NH
Handle Type:	detach
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Product Main Type:	EasyLine
Product Name:	Fuse Switch Disconnecter
Rated Current ( $I_n$ ):	Main Circuit 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	8 kV
Rated Operational Current AC-21B ( $I_e$ ):	(690 V) 200.0 A
Rated Operational Current AC-22B ( $I_e$ ):	(500 V) 250.0 A
Rated Operational Current AC-23B ( $I_e$ ):	(500 V) 250 A

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SEC312011B0202
Declaration of Conformity - CE:	1SEP500028P0001

## Classifications

ETIM 4:	EC001040 - Fuse switch disconnecter
ETIM 5:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q
UNSPSC:	39121600