



Electric Automation
Automation specialists

Reference: XLP000-6BC
Code: 1SEP201428R0001

100 A incl. 6 Cage Clamps

Buy it at Electric Automation Network



XLP000-6CC

Ordering

EAN:	7025840013372
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363000

Dimensions

Product Net Width:	0.09 m
Product Net Height:	0.152 m
Product Net Depth:	0.08 m
Product Net Weight:	0.46 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.09 m
Package Level 1 Height:	0.152 m
Package Level 1 Length:	0.08 m
Package Level 1 Gross Weight:	0.46 kg

Package Level 2 EAN:	7025840013372
----------------------	---------------

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2006-07-01
--------------	--

Additional Information

Degree of Protection:	acc. to IEC 60529 Front IP30
Frequency (f):	50/60 Hz
Fuse Protected Short-Circuit Making:	50 kiloampere rms
Fuse Protected Short-Circuit Withstand:	50 kiloampere rms
Fuse Size:	000
Fuse System:	DIN
Fuse Type:	NH
Handle Type:	detach
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Product Main Type:	EasyLine
Product Name:	Fuse Switch Disconnecter
Rated Current (I _n):	Main Circuit 100 A
Rated Impulse Withstand Voltage (U _{imp}):	6 kV
Rated Operational Current AC-21B (I _e):	(690 V) 50 A
Rated Operational Current AC-22B (I _e):	(500 V) 100.0 A
Rated Operational Current AC-23B (I _e):	(380 ... 415 V) 80.0 A
Terminal Type:	Spring Terminals

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SEC312011B0202
Declaration of Conformity - CE:	1SEP500026P0001

Classifications

E-nummer:	2307300
ETIM 4:	EC001040 - Fuse switch disconnecter
ETIM 5:	EC001040 - Fuse switch disconnecter
Object Classification Code:	Q
UNSPSC:	39121600