



Electric Automation
Automation specialists

Reference: MP1-7015
Code: 1SFA611100R7015

MP1-7015 Pushbutton

[Buy it at Electric Automation Network](#)



Modular Pushbutton - Momentary - Flush - White - Non-illuminated - Black plastic - 1NO

Ordering

EAN:	7320500311615
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369001

Dimensions

Product Net Width:	0.029 m
Product Net Height:	0.029 m
Product Net Depth:	0.033 m
Product Net Weight:	0.017 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.11 m
Package Level 1 Height:	0.029 m
Package Level 1 Length:	0.15 m
Package Level 1 Gross Weight:	0.017 kg

Environmental

Ambient Air Temperature:	Operation -25 ... +70 °C Storage -30 ... +85 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Actuator Type:	Flush
Bezel Material:	Black plastic
Block:	1NO
Color:	White
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Device:	Holder for blocks incl.
Function:	Momentary
IIT Publishing Status:	Level 0 - Information enabled
Illumination:	Non-illuminated
Mechanical Durability:	2 million
Number of Auxiliary Contacts NO:	1
Product Main Type:	MP1
Product Name:	Pushbutton
Product Range:	Modular
Product Type:	MP
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Operational Current AC-15 (I _e):	(220 / 240 V) 6 A (24 / 127 V) 8 A
Rated Operational Current DC-13 (I _e):	(125 V) 1.1 A (24 V) 5 A
RoHS Date:	0635 4
Symbol / Text:	I

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SFC151003C0201
Declaration of Conformity - CE:	1SFA1-83
RoHS Information:	1SFC151011D0203

Classifications

ETIM 4:	EC002024 - Accessories for control circuit devices
ETIM 5:	EC002024 - Accessories for control circuit devices

Object Classification Code:	S
UNSPSC:	39121512