Electric Automation
Automation specialists

Reference: CP3-10U-01
Code: 1SFA619102R1047

PUSHBUTTON#CP3-10U-01

Buy it at Electric Automation Network

Compact Pushbutton - Momentary - Extended - Grey - Non-illuminated - Black plastic - 1NC

Ordering

EAN:	7320500243015
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369001

Dimensions

Product Net Width:	0.030 m
Product Net Height:	0.030 m
Product Net Depth:	0.060 m
Product Net Weight:	0.019 kg

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	0.1 m
Package Level 1 Height:	0.03 m
Package Level 1 Length:	0.1 m
Package Level 1 Gross Weight:	0.019 kg

Package Level 2 Units:	10

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Actuator Type:	Extended
Bezel Material:	Black plastic
Block:	1NC
Color:	Grey
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Function:	Momentary
IIT Publishing Status:	Level 0 - Information enabled
Illumination:	Non-illuminated
Mechanical Durability:	0.5 million
Number of Auxiliary Contacts NC:	1
Product Main Type:	CP3
Product Name:	Pushbutton
Product Range:	Compact
Product Type:	CP
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Operational Current AC-15 (I_e):	(220 / 240 V) 1 A (24 / 127 V) 1.5 A
Rated Operational Current DC-13 (I_e):	(125 V) 0.2 A (24 V) 0.3 A
RoHS Date:	0626 5

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SFC151003C0201
Declaration of Conformity - CE:	1SFA1-70
RoHS Information:	1SFC151012D0202

Classifications

ETIM 4:	EC002024 - Accessories for control circuit devices
ETIM 5:	EC002024 - Accessories for control circuit devices

Object Classification Code:	S