



Electric Automation
Automation specialists

Reference: UA95-30-11
Code: 1SFL431022R8011

UA95-30-11 220-230V 50Hz / 230-240V
60Hz Contactor

Buy it at Electric Automation Network



A 3-phase Contactor suitable for Capacitor switching application. Maximum permissible peak current 30 times the nominal RMS current. Operated with a control voltage, versions from 24V to 690 V

Ordering

EAN:	7320500149478
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	102.0 mm
Product Net Depth:	123.5 mm
Product Net Height:	148.0 mm
Product Net Weight:	2.040 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	140 mm
Package Level 1 Length:	140 mm
Package Level 1 Height:	170 mm
Package Level 1 Gross Weight:	2 kg
Package Level 1 EAN:	7320500149478

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Rated Operational Voltage:	Main Circuit 1000 V
Rated Frequency (f):	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $\theta = 40\text{ °C}$ 145 A
Rated Short-time Withstand Current (I_{cw}):	<p>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 500 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 160 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 800 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1320 A</p> <p>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 350 A</p>
Maximum Breaking Capacity:	<p>$\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 440 V 1160 A</p> <p>$\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 690 V 800 A</p>
Maximum Electrical Switching Frequency:	240 cycles per hour
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Mechanical Durability:	10 million
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) $0.85 \times U_c$ Min. ... $1.1 \times U_c$ Max. (at $\theta \leq 70\text{ °C}$) °C
Rated Control Circuit Voltage (U_c):	60 Hz 230 ... 240 V 50 Hz 220 ... 230 V
Coil Consumption:	<p>Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A</p> <p>Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A</p> <p>Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A</p> <p>Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A</p>
Operate Time:	<p>Between Coil Energization and NO Contact Closing 10 ... 25 ms</p> <p>Between Coil De-energization and NO Contact Opening 10 ... 18 ms</p> <p>Between Coil De-energization and NC Contact Closing 7 ... 15 ms</p> <p>Between Coil Energization and NC Contact Opening 7 ... 22 ms</p>
Connecting Capacity-Main Circuit:	<p>Flexible with Cable End $1 \times 10 \dots 70\text{ mm}^2$</p> <p>Bar 30 mm^2</p> <p>Rigid $1 \times 10 \dots 95\text{ mm}^2$</p>

Connecting Capacity-Auxiliary Circuit:	Solid 2x1...4 mm ² Flexible with Insulated Ferrule 2x0.75...2.5 mm ² Stranded 2x1...4 mm ² Flexible 1x0.75...2.5 mm ² Flexible with Ferrule 2x0.75...2.5 mm ²
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting terminals (delivered in open position) Main poles:	M8 hexagon socket screw with single connector
Terminal Type:	Cable Clamp

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25...+50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40...+70 °C Close to Contactor for Storage -60...+80 °C
Maximum Operating Altitude Permissible:	3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B2 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B1 5 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C1 20 g
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
-----------------------------------	--------------------

Certificates and Declarations (Document Number)

CB Certificate:	SE-72472
CCC Certificate:	CQC_2003010304088242
Declaration of Conformity - CE:	1SFA1-63
RoHS Information:	1SFC101046D0203

Classifications

ETIM 5:	EC001079 - Capacitor magnet contactor
UNSPSC:	39121529