



Electric Automation
Automation specialists

Reference: CC-U/TCR
Code: 1SVR040015R2100

CC-U/TCR Universal signal converter
110-240VAC 50/60Hz / 100-300VDC

Buy it at [Electric Automation Network](#)



The CC-U/TCR is an universal signal converter from the CC-U range. This converter, with relay outputs and with 3-way electrical isolation, for thermocouples types K, J, T, and S, operates with a rated control supply voltage of 110-240 V AC and provides pluggable connecting terminals. The temperature ranges for the 4 different thermocouples as well as open- or closed-circuit operating principle can be configured by means of directly accessible lateral DIP switches. This converter has 2 threshold relay outputs with one c/o (SPDT) contact each. The threshold values and the respective hysteresis can be adjusted independently from each other with front-face potentiometers. Applied supply voltage is displayed by a green LED and two yellow LEDs display the state of the output relays.

Ordering

EAN:	4013614351495
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	109 mm
Package Level 1 Length:	26 mm
Package Level 1 Height:	124 mm
Package Level 1 Gross Weight:	0.171 kg

Dimensions

Product Net Width:	22.5 mm
Product Net Height:	105 mm
Product Net Depth:	120 mm
Product Net Weight:	0.145 kg

Technical

Function:	Thermocouple signals Universal
Input Signal:	TC sensors type J, K, T, S
Output Signal:	2 x 1 c/o (SPDT) contact
Rated Control Supply Voltage (U _s):	100-300 V DC 110-240 V AC

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Certificates and Declarations (Document Number)

CB Certificate:	CB_DK-9293
CCC Certificate:	CCC_2006010303193065
cUL Certificate:	cUL_Certificate_CC_relay output
Declaration of Conformity - CE:	1SAD938501-0075
RoHS Information:	1SAA981010-4403
UL Certificate:	UL_Certificate_CC_relay output

Classifications

Object Classification Code:	T
ETIM 4:	EC002653 - Isolation amplifier
ETIM 5:	EC002653 - Isolation amplifier
UNSPSC:	39120000
eClass:	7.0 27210120