



Electric Automation
Automation specialists

Reference: Borna relé CR-S230
Code: 1SVR405541R7210

CR-S230VADC1CRZ Interface relay cpl. 1c/o, A1-A2=230VAC/DC, Output=6A/250VAC

[Buy it at Electric Automation Network](#)



CR-S230VADC1CRZ Interface relay cpl. 1c/o, A1-A2=230VAC/DC, Output=6A/250VAC spring terminals

Ordering

EAN:	4013614499388
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	6.2 mm
Product Net Height:	76.6 mm
Product Net Depth:	94.7 mm
Product Net Weight:	0.03 kg

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	93 mm
Package Level 1 Height:	81 mm
Package Level 1 Length:	66 mm
Package Level 1 Gross Weight:	0.32 kg

Package Level 1 EAN:	4013614486753
----------------------	---------------

Technical

Function:	Fully assembled interface relay CR-S
Sub-Function:	Relay with standard contacts
Output:	1 c/o (SPDT) contact
Output Signal:	250 V / 6 A
Rated Control Supply Voltage (U _s):	230 V AC/DC
Terminal Type:	Spring Terminals

Environmental

Ambient Air Temperature:	Operation -40 ... +55 °C Storage 0 ... +40 °C
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Connecting Capacity UL/CSA:	Flexible 14 AWG Rigid 14 AWG
Tightening Torque UL/CSA:	4.42 in·lb

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_262671-2785865
cUR Certificate:	cUR_E244330 cUR_E244328
Declaration of Conformity - CE:	1SAD938500-0218
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
RoHS Information:	1SAA981068-4401
UR Certificate:	UR_E244330 UR_E244328

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
eClass:	7.0 27371601