



Electric Automation
Automation specialists

Reference: CR-P110DC2
Code: 1SVR405601R8000

CR-P110DC2 Pluggable interface relay
2c/o, A1-A2=110VDC, 250V/8A

Buy it at [Electric Automation Network](#)



The CR-P110DC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 110 V DC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

Ordering

EAN:	4013614498305
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	12.7 mm
Product Net Height:	15.7 mm
Product Net Depth:	29 mm
Product Net Weight:	0.014 kg

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	332 mm
Package Level 1 Height:	28 mm

Package Level 1 Length:	17 mm
Package Level 1 Gross Weight:	0.157 kg
Package Level 1 EAN:	4013614373046

Technical

Function:	Pluggable pcb interface relay CR-P
Sub-Function:	Relay w/o built in LED
Output:	2 c/o (SPDT) contacts
Output Signal:	250 V / 8 A
Rated Control Supply Voltage (U _s):	110 V DC

Environmental

RoHS Status:	Following EU Directive 2011/65/EC
--------------	-----------------------------------

Certificates and Declarations (Document Number)

CCC Certificate:	CCC_2007010303228779
CSA Certificate:	CSA_1587291
cUR Certificate:	cUR_E244330
Declaration of Conformity - CE:	1SAD938501-0159
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
GOST Certificate:	GOST_POCC_DE.AB76.D02256
RMRS Certificate:	RMRS_12.04008.250
RoHS Information:	1SAA981040-4404
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40019129

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
UNSPSC:	39121500
eClass:	7.0 27371601