



**Electric Automation**  
Automation specialists

Reference: CR-M024AC4  
Code: 1SVR405613R0000

CR-M024AC4 Pluggable interface relay 4c/o, A1-  
A2=24VAC, 250V/6A

Buy it at Electric Automation Network



The CR-M024AC4 pluggable interface relay is from the CR-M (miniature) relay range. This relay operates with a 24 V AC rated control supply voltage and has a 4 c/o (SPDT) output with contacts rated at 250 V / 6 A. The relay has an integrated orange test button for manual actuation and locking of the output contacts. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

## Ordering

|                         |               |
|-------------------------|---------------|
| EAN:                    | 4013614497698 |
| Minimum Order Quantity: | 10 piece      |
| Customs Tariff Number:  | 85364900      |

## Dimensions

|                     |          |
|---------------------|----------|
| Product Net Width:  | 21.2 mm  |
| Product Net Height: | 35.6 mm  |
| Product Net Depth:  | 27.5 mm  |
| Product Net Weight: | 0.033 kg |

## Container Information

|                        |          |
|------------------------|----------|
| Package Level 1 Units: | 10 piece |
|------------------------|----------|

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Width:        | 114 mm        |
| Package Level 1 Height:       | 61 mm         |
| Package Level 1 Length:       | 50 mm         |
| Package Level 1 Gross Weight: | 0.35 kg       |
| Package Level 1 EAN:          | 4013614373497 |

## Technical

|   |  |
|---|--|
| Function:                                       | Pluggable miniature interface relay CR-M |
| Sub-Function:                                   | Relay w/o built in LED                   |
| Output:   | 4 c/o (SPDT) contacts                    |
| Output Signal:                                  | 250 V / 6 A                              |
| Rated Control Supply Voltage (U <sub>s</sub> ): | 24 V AC                                  |

## Environmental

|              |                                   |
|--------------|-----------------------------------|
| RoHS Status: | Following EU Directive 2011/65/EC |
|--------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                 |                          |
|---------------------------------|--------------------------|
| CCC Certificate:                | CCC_2014010303720193     |
| CSA Certificate:                | CSA_2735700              |
| cUR Certificate:                | cUR_E244330              |
| Declaration of Conformity - CE: | 1SAD938501-0159          |
| EAC Certificate:                | EAC_RU_C-PL.ME77.B.01873 |
| GOST Certificate:               | GOST_POCC_DE.AB76.D02256 |
| LR Certificate:                 | LR_05_20002_E3           |
| RMRS Certificate:               | RMRS_12.04008.250        |
| RoHS Information:               | 1SAA981040-4404          |
| UR Certificate:                 | UR_E244330               |
| VDE Certificate:                | VDE_40040327             |

## Classifications

|                             |                            |
|-----------------------------|----------------------------|
| Object Classification Code: | K                          |
| E-nummer:                   | 4005350                    |
| ETIM 4:                     | EC001437 - Switching relay |
| ETIM 5:                     | EC001437 - Switching relay |
| UNSPSC:                     | 39121500                   |
| eClass:                     | 7.0 27371601               |

