



**Electric Automation**  
Automation specialists

Reference: CR-M220DC4LG  
Code: 1SVR405618R9100

CR-M220DC4LG Pluggable interface relay 4c/o,  
A1-A2=220VDC, gold plated contacts

Buy it at [Electric Automation Network](#)



The CR-M220DC4LG pluggable interface relay is from the CR-M (miniature) relay range. This relay operates with a 220 V DC rated control supply voltage and has a 4 c/o (SPDT) gold-plated output with contacts rated at 250 V / 6 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts and an integrated LED. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories

## Ordering

EAN:	4013614498114
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900

## Dimensions

Product Net Width:	21.2 mm
Product Net Height:	35.6 mm
Product Net Depth:	27.5 mm
Product Net Weight:	0.033 kg

## Container Information

Package Level 1 Units:	10 piece
------------------------	----------

Package Level 1 Width:	114 mm
Package Level 1 Height:	61 mm
Package Level 1 Length:	50 mm
Package Level 1 Gross Weight:	0.35 kg
Package Level 1 EAN:	4013614375682

## Technical

Function:	Pluggable miniature interface relay CR-M
Sub-Function:	Relay with built in LED and gold-plated contacts
Output:	4 c/o (SPDT) contacts
Output Signal:	250 V / 6 A
Rated Control Supply Voltage (U <sub>s</sub> ):	220 V DC

## Environmental

RoHS Status:	Following EU Directive 2011/65/EC
--------------	-----------------------------------

## Certificates and Declarations (Document Number)

CCC Certificate:	CCC_2014010303720193
CSA Certificate:	CSA_2735700
cUR Certificate:	cUR_E244330
Declaration of Conformity - CE:	1SAD938501-0159
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
GOST Certificate:	GOST_POCC_DE.AB76.D02256
LR Certificate:	LR_05_20002_E3
RMRS Certificate:	RMRS_12.04008.250
RoHS Information:	1SAA981040-4404
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40040327

## Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
UNSPSC:	39121500
eClass:	7.0 27371601