



Electric Automation
Automation specialists

Reference: CP-D 24/2.5
Code: 1SVR427044R0200

CP-D 24/2.5 Power supply In:
100-240VAC Out: 24VDC/2.5A

Buy it at [Electric Automation Network](#)



The CP-D 24/2.5 is a power supply from the CP-D range. The primary switch mode power supply offers a wide range input of 90-264 V AC and 120-375 V DC, rated input voltage is 100-240 V AC. The rated output power is 60 W, rated output current is 2.5 A at an output voltage of 24 V DC. The output voltage is adjustable within a range of 24 to 28 V DC. The power supply provides a U/I output characteristic.

Ordering

EAN:	4016779661188
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85044090

Dimensions

Product Net Width:	71 mm
Product Net Height:	91 mm
Product Net Depth:	57.5 mm
Product Net Weight:	0.252 kg

Container Information

Package Level 1 Width:	91 mm
Package Level 1 Length:	134 mm

Package Level 1 Height:	87 mm
Package Level 1 Gross Weight:	0.311 kg
Package Level 1 Units:	1 piece

Technical

Function:	Switch mode power supply
Number of Phases:	1
Input Voltage (U_{in}):	90 ... 264 V AC 120 ... 375 V DC
Output Voltage (U_{out}):	24 V DC
Output Current:	2.5 A
Output Power:	60 W

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Certificates and Declarations (Document Number)

CB Certificate:	CB_JPTUV-058481
CCC Certificate:	CCC_2007020907000169
cUL Certificate:	cUL508_E174460
cUR Certificate:	cUR60950_E196145 cUR1310_E313203
Declaration of Conformity - CE:	1SAD938503-0132
EAC Certificate:	EAC_RU_C-DE.ME77.B.01651
GOST Certificate:	GOST_POCC_CN.AB76.B00924
RoHS Information:	1SAA981047-4402
UL Certificate:	UL508_E174460
UR Certificate:	UR60950_E196145 UR1310_E313203

Classifications

eClass:	7.0 27049002
ETIM 4:	EC002540 - DC-power supply
ETIM 5:	EC002540 - DC-power supply
Object Classification Code:	T
UNSPSC:	39121100