



**Electric Automation**  
Automation specialists

Reference: CT-AKE  
Code: 1SVR550519R4000

CT-AKE Time relay, OFF-delay solid-state,  
1n/o, 0.3-30s, 24-240VAC

Buy it at [Electric Automation Network](#)



The CT-AKE is a single-function electronic time relay from the CT-E timer range. It provides an OFF-delay (delay on break) function with a time range from 0.3 s to 30 s. This time relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a solid-state output.

### Ordering

EAN:	4013614346705
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	84.2 mm
Package Level 1 Length:	24.6 mm
Package Level 1 Height:	83.1 mm
Package Level 1 Gross Weight:	0.066 kg

### Dimensions

Product Net Width:	22.5 mm
Product Net Height:	78 mm

Product Net Depth:	78.5 mm
Product Net Weight:	0.055 kg

## Technical

Timer Relay Type:	OFF-Delay
Time Range:	0.3-30 s
Rated Control Supply Voltage (U <sub>s</sub> ):	24 ... 240 V AC
Output:	solid-state output
Terminal Type:	Screw Terminals
Standards:	IEC 61812-1 EN 61812-1 + A11 DIN VDE 0435 part 2021

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Certificates and Declarations (Document Number)

cUL Certificate:	cUL508_E140448
Declaration of Conformity - CE:	1SAD938501-0114
EAC Certificate:	EAC_RU_C-DE.ME77.B.02016
GL Certificate:	GL_94633-94HH
GOST Certificate:	GOST_8572616
RMRS Certificate:	RMRS_12.04010.250
RoHS Information:	1SAA981001-4404
UL Certificate:	UL508_E140448

## Classifications

Object Classification Code:	K
ETIM 4:	EC001439 - Timer relay
ETIM 5:	EC001439 - Timer relay
UNSPSC:	39121500
eClass:	7.0 27371790