



Electric Automation
Automation specialists

Reference: ZLS905E64-3L
Code: 2CCA183144R0001

ZLS905E64-3L Starter pack Touch proof
with 64 Modules 3L



Buy it at [Electric Automation Network](#)

Starter pack Touch proof with 64 Modules L1,L2,L3 Pluggable socket system is completely fingersafe (IP2XB) together with the socket end piece

Ordering

| | |
|-------------------------|---------------|
| EAN: | 7612271413774 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85389030 |

Dimensions

| | |
|---------------------|-----------|
| Product Net Width: | 90 mm |
| Product Net Height: | 28.5 mm |
| Product Net Depth: | 1186.7 mm |
| Product Net Weight: | 1.949 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 132 mm |
| Package Level 1 Height: | 67 mm |
| Package Level 1 Length: | 1197 mm |
| Package Level 1 Gross Weight: | 2.068 kg |
| Package Level 1 EAN: | 7612271413774 |

Environmental

| | |
|--------------|---|
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|--------------|---|

Additional Information

| | |
|----------------------------|--|
| Product Main Type: | Accessories for Plug-in Distribution Systems |
| Product Name: | Accessories for Plug-in Distribution Systems |
| Rated Operational Voltage: | 690 V AC 1000 V DC |
| Standards: | EN 60439-1, EN60439-2 |

Certificates and Declarations (Document Number)

| | |
|------------------------------------|-----------------|
| Data Sheet, Technical Information: | 2CCC451059C0202 |
| Declaration of Conformity - CE: | 2CCC451023D0601 |
| RoHS Information: | 2CCC451021D0201 |

Classifications

| | |
|-----------------------------|-------------------|
| ETIM 4: | EC001522 - Busbar |
| ETIM 5: | EC001522 - Busbar |
| Object Classification Code: | W |