



**Electric Automation**  
Automation specialists

Reference: F402A25/0.01  
Code: 2CCF552100E0250

F402A25/0,01 Residual current operated  
circuit breaker 2 Poles 25A ~230/400V

Buy it at Electric Automation Network



F402A25/0,01 Residual current operated circuit breaker 2 Poles 25A - ~230/400V

#### Ordering

EAN:	7612270104420
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

#### Dimensions

Product Net Width:	36 mm
Product Net Height:	91 mm
Product Net Length:	72 mm
Product Net Depth:	75 mm
Product Net Weight:	0.250 kg

#### Container Information

Package Level 1 Units:	2 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	90 mm
Package Level 1 Length:	75 mm

Package Level 1 Gross Weight:	0.058 kg
Package Level 1 EAN:	7612270104420

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Additional Information

Frequency (f):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	2
Power Loss:	5.47 W
Product Main Type:	F402
Product Name:	F402
Rated Current (I <sub>n</sub> ):	25 A
Rated Operational Current (I <sub>e</sub> ):	25 A
Rated Operational Voltage:	230 / 400 V AC
Rated Residual Current:	0.01_AMPx
Rated Voltage (U <sub>r</sub> ):	230 / 400 V
Standards:	EN61008-1

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC451059C0202
Declaration of Conformity - CE:	2CCY451110D0601
RoHS Information:	2CCC451021D0201

## Classifications

ETIM 4:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:	EC002297 - Residual current circuit breaker (RCCB) module
Object Classification Code:	FB