



**Electric Automation**  
Automation specialists

Reference: F402A40/0.03  
Code: 2CCF552110E0400

F402A40/0,03 Residual current operated circuit breaker 2 Poles 40A ~230/400V

Buy it at [Electric Automation Network](#)



F402A40/0,03 Residual current operated circuit breaker 2 Poles 40A - ~230/400V

### Ordering

EAN:	7612270104444
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

### Dimensions

Product Net Width:	36 mm
Product Net Height:	91 mm
Product Net Length:	72 mm
Product Net Depth:	75 mm
Product Net Weight:	0.250 kg

### Container Information

Package Level 1 Units:	2 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	90 mm
Package Level 1 Length:	75 mm

Package Level 1 Gross Weight:	0.058 kg
Package Level 1 EAN:	7612270104444

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Additional Information

Frequency (f):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	2
Power Loss:	9.33 W
Product Main Type:	F402
Product Name:	F402
Rated Current (I <sub>n</sub> ):	40 A
Rated Operational Current (I <sub>e</sub> ):	40 A
Rated Operational Voltage:	230 / 400 V AC
Rated Residual Current:	0.03_AMPx
Rated Voltage (U <sub>r</sub> ):	230 / 400 V
Standards:	EN61008-1

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC451059C0202
Declaration of Conformity - CE:	2CCY451110D0601
RoHS Information:	2CCC451021D0201

## Classifications

E-nummer:	2161578
ETIM 4:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:	EC002297 - Residual current circuit breaker (RCCB) module
Object Classification Code:	FB