



Electric Automation
Automation specialists

Reference: S802PV-M32
Code: 2CCP812001R1329

High Performance Circuit Breaker -
S800PV-M - Disconnecter - Number of
poles 2 - Rated operational current 32A -
Rated operational voltage 800V DC

[Buy it at Electric Automation Network](#)



S802PV-M32 2 Pole DC main switch 32A 1.5kA 800VDC DC main switch

Ordering

EAN:	7612271211233
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

Dimensions

Product Net Width:	54 mm
Product Net Depth:	82.5 mm
Product Net Height:	95 mm
Product Net Weight:	0.43 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 1 Length:	60 mm
Package Level 1 Height:	99 mm
Package Level 1 Gross Weight:	0.45 kg

Package Level 1 EAN:	7612271211233
----------------------	---------------

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical

Standards:	IEC/EN 60947-3
Number of Poles:	2
Rated Current (I _n):	32
Rated Operational Voltage:	800 V DC
Power Loss:	1.8 W
Contact Position Indication:	ON / OFF / TRIP
Connecting Capacity:	Flexible 1 ... 50 mm ² Flexible Stranded 1 ...70 mm ²

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CCC413036D0601
RoHS Information:	2CCC413008D0201

Classifications

E-nummer:	2100001
ETIM 4:	EC000216 - Switch disconnecter
ETIM 5:	EC000216 - Switch disconnecter
Object Classification Code:	F