



Electric Automation
Automation specialists

Reference: S803S-SCL32-SR
Code: 2CCS803901R0539

S803S-SCL32-SR Self-resetting short-circuit current limiter 32A 3-pole tested acc. to IEC 60947-2

Buy it at Electric Automation Network



S803S-SCL32-SR Self-resetting short-circuit current limiter 32A 3-pole tested acc. to IEC 60947-2

Ordering

EAN:	7612271425609
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

Dimensions

Product Net Width:	81 mm
Product Net Height:	142 mm
Product Net Length:	27 mm
Product Net Depth:	82.5 mm
Product Net Weight:	0.75 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 1 Height:	99 mm
Package Level 1 Length:	86 mm

Package Level 1 Gross Weight:	0.78 kg
Package Level 1 EAN:	7612271425609

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Additional Information

Power Loss:	7.8 W
Product Main Type:	Accessories for High Performance Circuit Breakers HPCBs
Product Name:	High Performance Circuit Breakers HPCBs Accessories
Rated Current (I_n):	32 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Operational Current (I_e):	32 A
Rated Operational Voltage:	Auxiliary Circuit 400 / 690 V
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(240 / 415 V AC) 100 kA (254 / 440 V AC) 100 kA (289 / 500 V AC) 65 kA (400 / 690 V AC) 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(240 / 415 V AC) 100 kA (254 / 440 V AC) 100 kA (289 / 500 V AC) 65 kA (400 / 690 V AC) 50 kA
Standards:	IEC 60947-2 IEC 60947-4-1

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC413009B0201
Declaration of Conformity - CE:	2CCC413003C0202
RoHS Information:	2CCC413012D0601

Classifications

E-nummer:	2101580
ETIM 4:	EC000239 - Current limiter
ETIM 5:	EC000239 - Current limiter
Object Classification Code:	F