



Electric Automation
Automation specialists

Reference: S801S-K25
Code: 2CCS861001R0517

S801S-K25 High Performance Circuit
Breaker

[Buy it at Electric Automation Network](#)



The S801S-K25 is a 1-pole High Performance Circuit breaker with K-Characteristic, with cage terminal and a rated current of 25 A. It is a current limiting device with a maximum breaking capacity of 50kA at 240/415V. It can be used for voltages up to 400/690V and in DC as well. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S801S-K25 complies with IEC/EN 60898-1 and IEC/EN 60947-2 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S801S-K25 more comfortable. Due to the fast arc extinction of S801S-K25 your application will be secured.

Ordering

| | |
|-------------------------|---------------|
| EAN: | 7612271201487 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 85362020 |

Dimensions

| | |
|---------------------|---------|
| Product Net Width: | 27 mm |
| Product Net Depth: | 82.5 mm |
| Product Net Height: | 95 mm |
| Product Net Weight: | 0.25 kg |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 105 mm |
| Package Level 1 Length: | 33 mm |
| Package Level 1 Height: | 99 mm |
| Package Level 1 Gross Weight: | 0.27 kg |
| Package Level 1 EAN: | 7612271201487 |
| Package Level 2 Units: | 1 |

Environmental

| | |
|---|---|
| Ambient Air Temperature: | Operation -25 ... +60 °C Storage -40 ... +70 °C |
| Resistance to Vibrations acc. to IEC 60068-2-6: | 2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x Ie |
| Environmental Conditions: | Damp Heat Cyclic acc. to IEC 60068-2-30 12+12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96% Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100% Dry Heat Test B acc. to IEC 60068-2-2 16 hour @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hour @ 70 °C |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Technical

| | |
|--|---|
| Standards: | IEC/EN 60947-2 IEC/EN 60898-1 |
| Number of Poles: | 1 |
| Tripping Characteristic: | K |
| Rated Current (I_n): | 25 A |
| Rated Operational Voltage: | 400/690 V AC 125 V DC |
| Power Loss: | at Rated Operating Conditions per Pole 3.2 W |
| Rated Insulation Voltage (U_i): | 690 V AC |
| Rated Frequency (f): | 50 / 60 Hz |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}): | (240 / 415 V AC) 50 kA (254 / 440 V AC) 30 kA (400 / 690 V AC) 6 kA (125 V DC) 30 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}): | (240 / 415 V AC) 40 kA (254 / 440 V AC) 22.5 kA (400 / 690 V AC) 4 kA (125 V DC) 30 kA |
| Overvoltage Category: | IV |

| | |
|--|---|
| Pollution Degree: | 3 |
| Rated Impulse Withstand Voltage (U _{imp}): | 8 kV |
| Housing Material: | Insulation group I, RAL 7035 |
| Contact Position Indication: | ON / OFF / TRIP |
| Degree of Protection: | acc. to IEC 60529 IP20 |
| Remarks: | Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw |
| Electrical Endurance: | 10000 cycle |
| Mechanical Endurance: | 10000 cycle |
| Terminal Type: | Screw Terminals |
| Connecting Capacity: | Stranded 1 ... 50 mm ² Flexible 1 ...70 mm ² |
| Tightening Torque: | 3.5 N·m 31 in·lb |
| Recommended Screw Driver: | Pozidriv 2 |
| Mounting on DIN Rail: | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position: | Any |

Certificates and Declarations (Document Number)

| | |
|---------------------------------|-----------------|
| Declaration of Conformity - CE: | 2CCC413016D060 |
| RoHS Information: | 2CCC413008D0204 |

Classifications

| | |
|-----------------------------|--|
| ETIM 4: | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 5: | EC000042 - Miniature circuit breaker (MCB) |
| Object Classification Code: | F |