



Electric Automation
Automation specialists

Reference: F202B-63/0,03
Code: 2CSF202592R1630

F202 B-63/0,03 Residual Current Dev.

Buy it at Electric Automation Network



The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is particularly suitable for the protection against smooth d.c. earth fault currents.

Ordering

EAN:	8012542629634
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030

Dimensions

Product Net Width:	0.035 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.500 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.073 m
Package Level 1 Height:	0.078 m

Package Level 1 Length:	0.05 m
Package Level 1 Gross Weight:	0.350 kg
Package Level 1 EAN:	8012542629634

Technical

Standards:	EN 61008
Operating Characteristic:	Instantaneous
Type of Residual Current:	B type
Rated Residual Current:	30 mA
Rated Current (I_n):	63 A
Number of Poles:	2
Position of Neutral Terminals:	Right
Power Loss:	at Rated Operating Conditions per Pole 4.22 W

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CSC423009D2701
RoHS Information:	2CSC423006K2701

Classifications

Object Classification Code:	Q
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)