



Electric Automation
Automation specialists

Reference: RD3M
Code: 2CSJ202001R0002

RD3M - Residual Current Monitor

Buy it at Electric Automation Network



The RD3 series of electronic residual current relays provides residual current protection and monitoring functions. This device can be used in conjunction with all MCBs of S200 series and Tmax range moulded case devices up to T5, for industrial installations.

Ordering

EAN:	8012542747031
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364190

Dimensions

Product Net Width:	0.058 m
Product Net Height:	0.085 m
Product Net Depth:	0.058 m
Product Net Weight:	0.223 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.091 m
Package Level 1 Height:	0.09 m

Package Level 1 Length:	0.092 m
Package Level 1 Gross Weight:	0.307 kg
Package Level 1 EAN:	8012542747031

Technical

Standards:	IEC EN 60947-2 Ann M
Mounting Type:	DIN-rail
Rated Operational Voltage:	230 ... 400 V AC
Dimensions:	3 modules
Power Loss:	at Rated Operating Conditions per Pole 3.6 W

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	ITSCE167RD3
RoHS Information:	2CSC444010K0201

Classifications

Object Classification Code:	Q
ETIM 4:	EC001445 - Residual current monitoring relay
ETIM 5:	EC001445 - Residual current monitoring relay