



Electric Automation
Automation specialists

Reference: RD2-48
Code: 2CSM242120R1201

RD2-48 Residual Current Monitor

Buy it at Electric Automation Network



Residual current monitors (RCMs) with external transformer can detect leakage currents. Through minidip you can set sensitivity and intervention time. Operating voltage: 48...150V a.c./d.c.

Ordering

EAN:	8012542537809
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364190

Dimensions

Product Net Width:	0.035 m
Product Net Height:	0.085 m
Product Net Depth:	0.065 m
Product Net Weight:	0.105 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.041 m
Package Level 1 Height:	0.08 m
Package Level 1 Length:	0.103 m

Package Level 1 Gross Weight:	0.15 kg
Package Level 1 EAN:	8012542537809

Technical

Standards:	IEC EN 62020
Mounting Type:	DIN-rail
Rated Operational Voltage:	48 ... 150 V AC/DC
Dimensions:	2 modules
Power Loss:	at Rated Operating Conditions per Pole 3.4 W

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	ITSCE041RD-TRM
---------------------------------	----------------

Classifications

Object Classification Code:	Q
ETIM 4:	EC001445 - Residual current monitoring relay
ETIM 5:	EC001445 - Residual current monitoring relay