



**Electric Automation**  
Automation specialists

Reference: ISOL-DIG-PLUS  
Code: 2CSM341000R1501

ISOLTESTER-DIG-PLUS Insulation monitor

Buy it at Electric Automation Network



Provide protection from indirect contacts in IT circuits without breaking the circuit at the first indirect contact. They are used mostly in systems where residual current devices are not allowed because a sudden service breaking could cause serious inconveniences.

### Ordering

EAN:	8012542884606
Minimum Order Quantity:	1 piece
Customs Tariff Number:	90303100

### Dimensions

Product Net Width:	0.090 m
Product Net Height:	0.105 m
Product Net Depth:	0.058 m
Product Net Weight:	0.250 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.09 m
Package Level 1 Height:	0.065 m

Package Level 1 Length:	0.105 m
Package Level 1 Gross Weight:	0.5 kg
Package Level 1 EAN:	8012542884606
Package Level 2 Units:	1 piece
Package Level 2 Gross Weight:	0.500 kg

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	ITSCE091ISOL
RoHS Information:	2CSC445001K0201

## Classifications

Object Classification Code:	F
ETIM 4:	EC001449 - Device for monitoring of safety-related circuits
ETIM 5:	EC001449 - Device for monitoring of safety-related circuits