



Electric Automation
Automation specialists

Reference: DS201LC6AC300
Code: 2CSR245040R3064

DS201 L C6 AC300 - RCBO

Buy it at Electric Automation Network



The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

Ordering

EAN:	8012542171805
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363010

Dimensions

Product Net Width:	0.035 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.239 kg

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	0.253 m

Package Level 1 Height:	0.088 m
Package Level 1 Length:	0.108 m
Package Level 1 Gross Weight:	1.446 kg
Package Level 1 EAN:	8012542171812

Technical

Standards:	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
Type of Residual Current:	AC type
Rated Residual Current:	300 mA
Tripping Characteristic:	C
Rated Current (I_n):	6 A
Number of Poles:	2
Number of Protected Poles:	1
Rated Short-Circuit Capacity (I_{cN}):	(230 / 400 V AC) 4.5 kA
Position of Neutral Terminals:	Right
Power Loss:	4.4 W

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CSC421001D2702
RoHS Information:	2CSC422002K0201

Classifications

Object Classification Code:	Q
ETIM 4:	EC000905 - Earth leakage circuit breaker
ETIM 5:	EC000905 - Earth leakage circuit breaker