



Electric Automation
Automation specialists

Reference: S2C-UA24DC
Code: 2CSS200911R0007

S2C-UA 24 DC - Undervoltage release

Buy it at Electric Automation Network



The S2C-UA 24 DC undervoltage release has the function to protect the load in case of a voltage drop included between 70% and 35% of its rated value. Positive safety (device tripping when the voltage is disconnected) emergency stop by means of a button. Suitable for MCBs S200 series, RCCBs F200 series and RCBOs DS201, DS202C, DS200 series. It can be used with MCBs SN201 series by means of SN201-IH interface module. Rated voltage: 24V d.c.

Ordering

EAN:	8012542896401
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

Dimensions

Product Net Width:	0.018 m
Product Net Height:	0.085 m
Product Net Depth:	0.074 m
Product Net Weight:	0.090 kg

Container Information

Package Level 1 Units:	1 piece
------------------------	---------

Package Level 1 Width:	0.125 m
Package Level 1 Height:	0.035 m
Package Level 1 Length:	0.11 m
Package Level 1 Gross Weight:	0.1 kg
Package Level 1 EAN:	8012542896401

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q4
--------------	---

Additional Information

Product Main Type:	S2C-UA
Product Name:	Undervoltage release
Suitable For:	S200 DS200 F200
Suitable for Product Class:	Miniature Circuit Breakers MCBs Residual Current Breakers with Overload Protection RCBo Residual Current Devices RCDs

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CSC400002D0209
Declaration of Conformity - CE:	ITSCE0161
RoHS Information:	2CSC490002K0201

Classifications

ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code:	Q