



Electric Automation
Automation specialists

Reference: OVRT24L40-275PQS
Code: 2CTB803873R5600

OVR T2 4L 40-275 P QS

Buy it at Electric Automation Network



OVR T2 4L 40-275 P QS

Ordering

Product Main Type:	T2
EAN:	3660308520548
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363090

Technical

Type of Low Voltage Distribution System:	TN-S
Nominal AC Voltage of the System (U_0):	230 / 400 V
Number of Protected Poles:	4
Arrester Class:	II
Standards:	IEC 61643-11 / EN 61643-11
Product Type:	QS
Remote Indicator:	No
Version:	Plug-in
Discharge Current (I_{max}):	Nominal 20 kA Maximum 40 kA Total 160 kA
Impulse Current:	2 kA

Maximum Continuous Operating Voltage (U _c):	(L-PE) 275 V (L-L) 440 V (L-N) 440 V (N-PE) 275 V
Voltage Rating DC:	350 V
Voltage Protection Level (U _p):	(L-N) - kV (N-PE) 1.25 kV (L-PE) 1.25 kV
Short Circuit Withstand I _{cc} :	100 kA
Temporary Overvoltage Test Value (U _T):	337 V
Short-Circuit Protective Devices:	Curve B Breakers ≤ 125 A Curve C Breakers ≤ 125 A gL Type Fuses ≤ 125 A gG Type Fuses ≤ 125 A
Auxiliary Circuit Load:	Minimum - Maximum -
Power Loss:	29 mW
Product Name:	Surge Protective Devices
Suitable For:	To protect the systems against the transient overvoltage (lightning)

Dimensions

Product Net Width:	71,2 mm
Product Net Depth:	58 mm
Product Net Height:	88 mm
Product Net Weight:	480 g
Width in Number of Modular Spacings:	4

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	117 mm
Package Level 1 Length:	77 mm
Package Level 1 Height:	82 mm
Package Level 1 Gross Weight:	500 g
Package Level 1 EAN:	3660308520548

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CTC432239D0201
Declaration of Conformity - CE:	2CTC436004G1701
Instructions and Manuals:	2CTC432096M1701

Classifications

ETIM 4:	EC000941 - Surge protection device for power supply systems
ETIM 5:	EC000941 - Surge protection device for power supply systems