



**Electric Automation**  
Automation specialists

Reference: OVRPV40-1500PBW  
Code: 2CTB804153R2200

OVR PV 40-1500 P BW

Buy it at Electric Automation Network

OVR PV 40-1500 P BW

#### Additional Information

|   |   |
|---|---|
| Arrester Class:                                 | II  |
| Catalog Description:                            | OVR PV 40-1500 P BW   |
| Country of Origin:                              | Bulgaria (BG)   |
| Customs Tariff Number:                          | 85354000  |
| Data Sheet, Technical Information:              | 2CTC432322D1701   |
| Declaration of Conformity - CE:                 | 2CTC436004G1701   |
| Discharge Current ( $I_{max}$ ):                | Nominal 15 kA<br>Maximum 40 kA                              |
| EAN:  | 3660308524843   |
| ETIM 4:   | EC000941 - Surge protection device for power supply systems |
| ETIM 5:   | EC000941 - Surge protection device for power supply systems |
| Impulse Current:                                | 2 kA  |
| Instructions and Manuals:                       | 2CTC432086M1701   |
| Invoice Description:                            | OVR PV 40-1500 P BW   |
| Maximum Continuous Operating Voltage ( $U_c$ ): | 1500 V  |
| Minimum Order Quantity:                         | 1 piece   |
| Number of Poles:                                | 2   |
| Number of Protected Poles:                      | 2   |
| Object Classification Code:                     | 141DCC  |
| Package Level 1 EAN:                            | 3660308524843   |
| Package Level 1 Gross Weight:                   | 400 g   |
| Package Level 1 Height:                         | 82 mm   |
| Package Level 1 Length:                         | 61 mm   |

|                                      |  |
|--------------------------------------|--|
| Package Level 1 Units:               | 1 piece  |
| Package Level 1 Width:               | 117 mm   |
| Product Main Type:                   | T2   |
| Product Name:                        | Surge Protective Devices   |
| Product Net Depth:                   | 58 mm  |
| Product Net Height:                  | 88 mm  |
| Product Net Weight:                  | 375 g  |
| Product Net Width:                   | 53.4 mm  |
| Remote Indicator:                    | No   |
| Selling Unit of Measure:             | piece  |
| Short Circuit Withstand Icc:         | 10 kA  |
| Short Description:                   | OVR PV 40-1500 P BW  |
| Standards:                           | IEC 61 643-11 / EN 50539-11  |
| Suitable For:                        | To protect the systems against the transient overvoltage (lightning) |
| Version:                             | Plug-in  |
| Voltage Protection Level ( Up):      | (L-N) 4,5 kV<br>(N-PE) 4,5 kV<br>(L-PE) 4,5 kV                       |
| Voltage Rating DC:                   | 1500 V   |
| Width in Number of Modular Spacings: | 3  |