



Electric Automation
Automation specialists

Reference: OVRT1-T212.5-275sC
Code: 2CTB815710R2600

OVR T1-T2 12.5-275s C QS

Buy it at Electric Automation Network



OVR T1-T2 12.5-275s C QS

Ordering

Product Main Type:	T1-T2
EAN:	3660308525031
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363090

Technical

Type of Low Voltage Distribution System:	TT TN-C TN-S
Nominal AC Voltage of the System (U_0):	230 / 400 V
Number of Protected Poles:	1
Arrester Class:	I II
Standards:	IEC 61643-11 / EN 61643-11
Product Type:	QS
Version:	Plug-in
Discharge Current (I_{max}):	Nominal 12.5 kA Maximum 80 kA
Impulse Current:	12.5 kA

Maximum Continuous Operating Voltage (U _c):	(L-PE) 275 V (L-L) 275 V (L-N) 275 V (N-PE) - V
Voltage Rating DC:	350 V
Short Circuit Withstand I _{cc} :	100 kA
Temporary Overvoltage Test Value (U _T):	337 V
Power Loss:	37 mW
Product Name:	Surge Protective Devices
Suitable For:	To protect the systems against the transient overvoltage (lightning)

Dimensions

Product Net Width:	17.6 mm
Product Net Depth:	67 mm
Product Net Height:	57 mm
Product Net Weight:	100 g
Width in Number of Modular Spacings:	1

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	117 mm
Package Level 1 Length:	25 mm
Package Level 1 Height:	82 mm
Package Level 1 Gross Weight:	115 g
Package Level 1 EAN:	3660308525031

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CTC436004G1701
Instructions and Manuals:	-

Classifications

ETIM 4:	EC001457 - Combined arrester for power supply systems
ETIM 5:	EC001457 - Combined arrester for power supply systems