



Electric Automation
Automation specialists

Reference: RT7 B
Code: 2TLA010028R1000

RT7B 3s 24DC Safety relay

Buy it at Electric Automation Network



A universal safety relay for many safety applications. 2 delayed outputs of 3 sec.
Relay outputs 2NO/2NO/1NC

Ordering

EAN:	7350024431957
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364110

Dimensions

Product Net Width:	0.045 m
Product Net Height:	0.084 m
Product Net Depth:	0.120 m
Product Net Weight:	0.405 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.131 m
Package Level 1 Height:	0.060 m
Package Level 1 Length:	0.091 m
Package Level 1 Gross Weight:	0.450 kg

Safety Information

Safety Category Acc. to ISO 13849-1:	4
--------------------------------------	---

Additional Information

Product Main Type:	RT
Product Name:	Safety Relay
Rated Control Supply Voltage (U _s):	24 V DC
Suitable For:	Interlocking switch/Gate/Hatch, Light curtains, Light beams, Safety mats, Contact strips, Emergency stop, Hold to run/Enabeling device, Foot control device, Area supervision, Output expansion, Delayed output

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2TLC172001C0202_chapter06
Declaration of Conformity - CE:	2TLC172078D0201

Classifications

E-nummer:	3861162
ETIM 4:	EC001449 - Device for monitoring of safety-related circuits
ETIM 5:	EC001449 - Device for monitoring of safety-related circuits
Object Classification Code:	K