



**Electric Automation**  
Automation specialists

Reference: JSTD1-G AS-i  
Code: 2TLA020007R3900

JSTD1-G AS-i Safeball 2x250mm cable

[Buy it at Electric Automation Network](#)

JSTD1-G AS-i Safeballs is a equipped with a safe node which makes it possible to connect to a AS-i system. The Safeball has an ergonomic design with several grip possibilities and low activation force (approx. 2N) and flexible mounting options. Provides highest level of safety for use in two hand control applications when using two Safeballs in conjunction with AS-i monitor like Pluto Safety PLC. IP67 protection degree, plastic body, 0.25m wires x 2 for direct connection into an enclosure.

### Ordering

EAN:	7350024460230
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365011

### Dimensions

Product Net Width:	0.072 m
Product Net Height:	0.071 m
Product Net Depth:	0.072 m
Product Net Weight:	0.120 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.185 m
Package Level 1 Height:	0.080 m
Package Level 1 Length:	0.105 m
Package Level 1 Gross Weight:	0.300 kg
Package Level 1 EAN:	7350024464351
Package Level 2 Units:	2 piece
Package Level 2 EAN:	7350024460230

## Safety Information

Performance Level (PL):	Up to e
Safety Category Acc. to ISO 13849-1:	4

## Additional Information

Product Main Type:	JSTD1
Product Name:	Two Hand Safety Control Device

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2TLC172001C0202_chapter10
Declaration of Conformity - CE:	2TLC172024D0201

## Classifications

ETIM 4:	EC002611 - Control switch
ETIM 5:	EC002611 - Control switch
Object Classification Code:	B