



Electric Automation
Automation specialists

Reference: AS-i
Code: 2TLA020070R1100

Pluto AS-i v2

Buy it at Electric Automation Network



Safety PLC with AS-i bus and Pluto safety bus. Totally 12 I/O: 4 failsafe inputs + 4 non-failsafe outputs/failsafe inputs + 2 individual failsafe relay outputs + 2 individual failsafe transistor outputs.

Ordering

EAN:	7320500410592
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364110

Dimensions

Product Net Width:	0.045 m
Product Net Height:	0.084 m
Product Net Depth:	0.120 m
Product Net Weight:	0.390 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.090 m
Package Level 1 Height:	0.057 m
Package Level 1 Length:	0.130 m

Package Level 1 Gross Weight:	0.420 kg
-------------------------------	----------

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Safety Information

Diagnostic Coverage:	High
Performance Level (PL):	Up to e
Safety Category Acc. to ISO 13849-1:	4

Additional Information

Product Main Type:	Pluto
Product Name:	Programmable Safety Controller
Rated Control Supply Voltage (U _s):	24 V DC
RoHS Date:	1101

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2TLC172001C0202_chapter02
Declaration of Conformity - CE:	2TLC172011D0201
RoHS Information:	2TLC172006D0201

Classifications

ETIM 4:	EC001449 - Device for monitoring of safety-related circuits
ETIM 5:	EC001449 - Device for monitoring of safety-related circuits
Object Classification Code:	K